


EN 50618 H1Z2Z2-K 62930 IEC 131 1x6.0mm² SOLAR CABLE

规格 (Specifications)

EN50618 H1Z2Z2-K 1x6.0mm²

截面图 (Cross Section Diagram)



结构 (Construction)

型号 Type	导体 (Conductor)		绝缘 (Insulation)		护套 (Jacket)	
	芯线结构 Wire struct (± 0.008)	导体直径 Conductor diameter	厚度 Thickness (mm)	直径 Diameter (mm)	厚度 Thickness (mm)	直径 Diameter (mm)
6.0mm ²	81/0.285	3.2	0.7	4.7±0.2	0.8	6.3±0.2

印字 (Marking)

EN 50618 H1Z2Z2-K 62930 IEC 131 HALOGEN FREE LOW SMOKE
1x6mm² DONGGUAN SLOCABLE SOLAR CABLE www.slocable.com.cn

备注 (Remark):

产品说明 (Product Description)

- Tinned copper stranded wire
- XLPE insulation, white color
- XLPE Jacket, black/red

参考标准 (Reference Standard)

- EN 50618:2014
- IEC 62930

订货料号 (Order No.):

CA106B-EN (BLACK)

CA106R-EN (RED)

电气性能 (Electrical Characteristics)

- 额定电压 (Rated voltage): 1500V DC
- 额定电流 (Rated current): 70A
- 最大导体温度 (Max. conductor temperature): +120°C
- 工作环境 (Ambient temperature): -40~+90°C
- 最大导体电阻 (Conductor Resistance (max.)): 6.0mm²: 3.39 Ω/km@20°C
- 绝缘强度 (Dielectric Strength (AC)): 6.5 KV/5Min.
- 使用寿命 (Expected period of use): ≥25 years

物理性能 (Physical Characteristics)

- 垂直燃烧 (Flame test): IEC60332-1-2
- 烟浓度 (Smoke density): IEC61034-2
- 无卤 (Halogen free): IEC62821-1
- 耐臭氧 (Ozone resistance): IEC60811-403
- 耐油 (Oil resistance): EN60811
- 抗紫外线 (UV resistant): IEC60811-501

客户签字/盖章
(Autograph/Seal):确认日期
(Date):

版本 (Rev.)

日期 (Date)

历史记录 (History Record)

A2.0

2023.03

/

编制

(Prepared By)

审核

(Reviewed By)

批准

(Approved By)

东莞市思普太阳能科技有限公司
Dongguan Slocable Photovoltaic Technology Co., Ltd

地址/Add: 广东省东莞市洪梅镇望沙路洪梅段9号之二2栋101室

Building 2, No. 9-2, Wangsha Road, Hongmei Town,

Dongguan City, Guangdong Province, China

电话/TEL: (+86)-769-22010201

网站/Website: http://www.slocable.com.cn